HEPCE CHEM Co., Ltd.

Product Information

www.hepce.com

IMPRESSION

HCP-150L

Antistatic Agent
for Polyurethane Foam System

CHARACTERISTICS

- Good antistatic properties(Surface resistance : 10^{11}-$10^{8}\Omega/cm^2$)
- 100% High-solid system.
- More effective with less quantity as compared with other agents. (Recommended addition weight : 2.0-5.0 part(wt/wt))
- Good mixed with urethane systems, and especially in case of two components urethane system, provides excellent durability by direct reaction.
- Available to make the various hues as colorless transparent liquid.

PROPERTIES

- Appearance : Colorless transparent liquid / 60°C (Wax phase in normal temperature)
- Viscosity : 25±50 cPS/60°C
- Density : 1.5±0.2 (g/cm^3)

APPLICATION

- Polyurethane Foaming System
- Polyurethane coating agent or casting system
- Applicable to other polymer resin(Acrylic resin, Rubbery resin, etc.)

HANDLING & STORAGE

- The self life of this agent is minimum one year in normal indoor.
- To be wax phase below 60°C, keep the wax phase enough until changing into liquid phase in oven at 70-110°C prior to use for your convenience when handling.
- In case of two components urethane system, addition to polyol mixture should be needed, because of the possibility of gelation by reaction with isocyanate functional group.
- Do not use near fire or flame.
- Store in well-ventilated place.
- Packing : 25kg Can

HEPCE CHEM Co., Ltd.
http://www.hepce.com
E-mail : hepce@hepce.com

H/O & Factory : TEL : +82-31-491-1611, FAX : +82-31-491-7400,
ShiWha Ind. 6BA-505, #683-4, Sunggok-dong, Ansan-City, Kyungki-Do, Korea, 425-836
R & D Center : TEL : +82-31-417-0662, FAX : +82-31-417-0111
RM No. 412, Ansan Technopark, #1271, Sa-dong, Ansan-City, Kyungki-Do, Korea, 425-791